

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

RG58 AU 90%

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

PRODUCT DESCRIPTION:

TINNED COPPER, FPE, BONDED LAMINATED ALUMINUM OR COPPER FOIL,
90% TINNED COPPER BRAID OR COPPER CLAD ALUMINUM, PVC

CENTER CONDUCTOR: 0.94 mm TINNED COPPER

DIELECTRIC:

GAS EXPANDED POLYETHYLENE

NOMINAL DIAMETER OVER DIELECTRIC: 2.95 mm

SHIELD:

1ST SHIELD: LAMINATED ALUMINUM TAPE BONDED
TO THE DIELECTRIC

2nd SHIELD: 96*0.12 mm TINNED COPPER BRAID
OR COPPER CLAD ALUMINUM BRAID

90% COVERAGE

JACKET:

PVC

NOMINAL DIAMETER OVER JACKET: 4.93 mm

NOMINAL JACKET THICKNESS: 0.76 mm

ELECTRICAL PROPERTIES:

IMPEDANCE: 50.0 +/- 2.0 Ohms

VELOCITY OF PROPAGATION: 66.0% NOMINAL



WANLONG CABLE

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

RG58 AU 90%

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

ATTENUATION @ 68°F (20°C):

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	1.0 dB	3.1 dB
10 MHz	1.3 dB	4.3 dB
50 MHz	3.1 dB	10.2 dB
100 MHz	4.5 dB	14.8 dB
200 MHz	6.6 dB	21.6 dB
400 MHz	10.0 dB	32.8 dB
700 MHz	14.2 dB	46.6 dB
900 MHz	16.6 dB	54.4 dB
1000 MHz	18.1 dB	59.3 dB