

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

SAT602

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

CENTER CONDUCTOR: 1.02 ± 0.01 MM BARE COPPER/COPPER CLAD STEEL

DIELECTRIC:

GAS EXPANDED POLYETHYLENE

NOMINAL DIAMETER OVER DIELECTRIC: 4.60 ± 0.05MM

SHIELD:

1st SHIELD: ALUMINUM FOIL

NON-BONDED/BONDED

2nd SHIELD: ALUMINUM BRAID WIRE

40%-90% COVERAGE

JACKET:

PVC JACKET

NOMINAL DIAMETER OVER JACKET: 6.80 ± 0.05 mm



ELECTRICAL PROPERTIES:

IMPEDANCE: 75.0 ± 3.0 Ohms

CAPACITANCE: 52 ± 2(pF/m)

VELOCITY OF PROPAGATION: 85.0% NOMINAL

RETURN LOSS:

5-1000MHz(dB) ≥ 22

1000-2000MHz(dB) ≥ 20

WANLONG CABLE

WANLONG CABLE

PROFESSIONAL CABLE MANUFACTURER

SAT602

Hangzhou Lin'an Wanlong Cable Co., Ltd

317 Jintian Road, Lin'an, Hangzhou, China 311300

Mob:+86-13968032911 Tel:+86-571-61078177

Fax:+86-571-61078123

Website: www.wanlongcable.cn

E-mail: wanlongcable@hotmail.com wanlongcable2@outlook.com

ATTENUATION @ 68°F. (20°C):

@ Frequency MHz	dB/100 ft. (MAX.)	dB/100 meters (MAX.)
5 MHz	0.58 dB	1.90 dB
50 MHz	1.50 dB	4.90 dB
100 MHz	2.16 dB	7.10 dB
200 MHz	2.74 dB	9.00 dB
400 MHz	3.96 dB	13.00 dB
800 MHz	5.70 dB	18.70 dB
1000 MHz	6.40 dB	21.00 dB
1350 MHz	7.77 dB	25.50 dB
1750 MHz	8.69 dB	28.50 dB
2150MHz	9.82 dB	32.20 dB
2400 MHz	10.67 dB	35.00 dB
3000MHz	12.37 dB	40.60 dB